


Safety Data Sheet

Gasoline, Unleaded

NFPA: Flammability



SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : Gasoline, Unleaded

Synonyms : Blend of Highly Flammable Petroleum Distillates, Regular, Mid-Grade, Premium, 888100008809

SDS Number : 888100008809 **Version** : 1.1

Product Use Description : Fuel


Company : For: Tesoro Refining & Marketing Co.
19100 Ridgewood Parkway, San Antonio, TX 78259

Tesoro Call Center : (877) 783-7676 **Chemtrec (Emergency Contact)** : (800) 424-9300

SECTION 2. HAZARDS IDENTIFICATION

Classifications : Flammable Liquid – Category 1 or 2 depending on formulation.
Aspiration Hazard – Category 1
Carcinogenicity – Category 2
Specific Target Organ Toxicity (Repeated Exposure) – Category 2
Specific Target Organ Toxicity (Single Exposure) – Category 3
Skin Irritation – Category 2
Eye Irritation – Category 2B
Chronic Aquatic Toxicity – Category 2

Pictograms :



Signal Word : **Danger**

Hazard Statements

Extremely flammable liquid and vapor.
May be fatal if swallowed and enters airways – do not siphon gasoline by mouth.
Suspected of causing blood cancer if repeated over-exposure by inhalation and/or skin contact occurs.
May cause damage to liver, kidneys and nervous system by repeated and prolonged inhalation or skin contact. Causes eye irritation. Can be absorbed through skin.
May cause drowsiness or dizziness. Extreme exposure such as intentional inhalation may cause unconsciousness, asphyxiation and death.
Repeated or prolonged skin contact can cause irritation and dermatitis.

Harmful to aquatic life.

Precautionary statements

Prevention

- : Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat, sparks, open flames, welding and hot surfaces.
- No smoking.
- Keep container tightly closed.
- Ground and/or bond container and receiving equipment.
- Use explosion-proof electrical equipment.
- Use only non-sparking tools (if tools are used in flammable atmosphere).
- Take precautionary measures against static discharge.
- Wear gloves, eye protection and face protection (as needed to prevent skin and eye contact with liquid).
- Wash hands or liquid-contacted skin thoroughly after handling.
- Do not eat, drink or smoke when using this product.
- Do not breathe vapors.
- Use only outdoors or in a well-ventilated area.

Response

- : In case of fire: Use dry chemical, CO₂, water spray or fire fighting foam to extinguish.
- If swallowed: Immediately call a poison center, doctor, hospital emergency room, medical clinic or 911. Do NOT induce vomiting. Rinse mouth.
- If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- If in eye: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- If skin or eye irritation persists, get medical attention.
- If inhaled: Remove person to fresh air and keep comfortable for breathing. Get medical attention if you feel unwell.

Storage

- : Store in a well ventilated place. Keep cool. Store locked up. Keep container tightly closed. Use only approved containers. Some containers not approved for gasoline may dissolve and release flammable gasoline liquid and vapors.

Disposal

- : Dispose of contents/containers to approved disposal site in accordance with local, regional, national, and/or international regulations.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Weight %
Gasoline, natural; Low boiling point naphtha	8006-61-9	10 - 30%
Toluene	108-88-3	10 - 30%
Xylene	1330-20-7	10 - 30%
Ethanol; ethyl alcohol	64-17-5	0-8.2%
Trimethylbenzene	25551-13-7	1 - 5%
Isopentane; 2-methylbutane	78-78-4	1 - 5%

Naphthalene	91-20-3	1 - 5%
Benzene	71-43-2	Less than 1.3%
Pentane	109-66-0	1 - 5%
Cyclohexane	110-82-7	1 - 5%
Ethylbenzene	100-41-4	1 - 5%
Butane	106-97-8	1 - 20%
Heptane [and isomers]	142-82-5	0.5 - 0.75%
N-hexane	110-54-3	0.5 - 0.75%

SECTION 4. FIRST AID MEASURES

Inhalation	: If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek medical attention immediately.
Skin contact	: In case of contact, immediately flush skin with plenty of water. Take off contaminated clothing and shoes immediately. Wash contaminated clothing before re-use. Contaminated leather, particularly footwear, must be discarded. Note that contaminated clothing may be a fire hazard. Seek medical advice if symptoms persist or develop.
Eye contact	: Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice if symptoms persist or develop.
Ingestion	: Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Obtain medical attention.
Notes to physician	: Symptoms: Dizziness, Discomfort, Headache, Nausea, Kidney disorders, Liver disorders. Aspiration may cause pulmonary edema and pneumonitis. Swallowing gasoline is more likely to be fatal for small children than adults, even if aspiration does not occur.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media	: SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO ₂ , water spray or fire fighting foam. LARGE FIRES: Water spray, fog or fire fighting foam. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers. Keep containers and surroundings cool with water spray.
Specific hazards during fire fighting	: Extremely flammable liquid and vapor. This material is combustible/flammable and is sensitive to fire, heat, and static discharge.
Special protective equipment for fire-fighters	: Firefighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH/MSHA- approved pressure-demand self-contained breathing apparatus with full facepiece and full protective clothing.

Further information

- : Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water. For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied fire fighting foam. Exposure to decomposition products may be a hazard to health. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6. ACCIDENTAL RELEASE MEASURES**Personal precautions**

- : Evacuate personnel to safe areas. Ventilate the area. Remove all sources of ignition. Response and clean-up crews must be properly trained and must utilize proper protective equipment (see Section 8).

Environmental precautions

- : Discharge into the environment must be avoided. If the product contaminates rivers and lakes or drains inform respective authorities.

Methods for cleaning up

- : Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations.

SECTION 7. HANDLING AND STORAGE**Precautions for safe handling**

- : Keep away from fire, sparks and heated surfaces. No smoking near areas where material is stored or handled. The product should only be stored and handled in areas with intrinsically safe electrical classification.

Hydrocarbon liquids including this product can act as a non-conductive flammable liquid (or static accumulators), and may form ignitable vapor-air mixtures in storage tanks or other containers. Precautions to prevent static-initiated fire or explosion during transfer, storage or handling, include but are not limited to these examples:

- (1) Ground and bond containers during product transfers. Grounding and bonding may not be adequate protection to prevent ignition or explosion of hydrocarbon liquids and vapors that are static accumulators.
- (2) Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil or diesel) is loaded into tanks previously containing low flash point products (such as gasoline or naphtha).
- (3) Storage tank level floats must be effectively bonded.

For more information on precautions to prevent static-initiated fire or explosion, see NFPA 77, Recommended Practice on Static Electricity (2007), and API Recommended Practice 2003, Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents (2008).

Conditions for safe storage, including incompatibilities

- : Keep away from flame, sparks, excessive temperatures and open flame. Use approved containers. Keep containers closed and clearly labeled. Empty or partially full product containers or vessels may contain explosive vapors. Do not pressurize, cut, heat, weld or expose containers to sources of ignition. Store in a well-ventilated area. The storage area should comply with NFPA 30 "Flammable and Combustible Liquid Code". The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 "Cleaning Mobile Tanks In Flammable and Combustible Liquid Service" and API RP 2015 "Cleaning Petroleum Storage Tanks".

Reports suggest that government-mandated ethanol, if present, may not be compatible with fiberglass gasoline tanks. Ethanol may dissolve fiberglass resin, causing engine damage and possibly allow leakage of explosive gasoline.

Keep away from food, drink and animal feed. Incompatible with oxidizing agents. Incompatible with acids.

No decomposition if stored and applied as directed. Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure. Store only in containers approved and labeled for gasoline.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

List	Components	CAS-No.	Type:	Value
OSHA	Benzene	71-43-2	TWA	1 ppm
		71-43-2	STEL	5 ppm
		71-43-2	OSHA_ACT	0.5 ppm
OSHA Z1	Xylene	1330-20-7	PEL	100 ppm 435 mg/m ³
	Ethanol; Ethyl alcohol	64-17-5	PEL	1,000 ppm 1,900 mg/m ³
	Naphthalene	91-20-3	PEL	10 ppm 50 mg/m ³
	Cyclohexane	110-82-7	PEL	300 ppm 1,050 mg/m ³
	Ethylbenzene	100-41-4	PEL	100 ppm 435 mg/m ³
	Heptane [and isomers]	142-82-5	PEL	500 ppm 2,000 mg/m ³
	N-hexane	110-54-3	PEL	500 ppm 1,800 mg/m ³
ACGIH	Toluene	108-88-3	TWA	50 ppm
	Xylene	1330-20-7	TWA	100 ppm
		1330-20-7	STEL	150 ppm
	Ethanol; Ethyl alcohol	64-17-5	TWA	1,000 ppm
	Trimethylbenzene	25551-13-7	TWA	25 ppm
	Isopentane; 2-Methylbutane	78-78-4	TWA	600 ppm
	Naphthalene	91-20-3	TWA	10 ppm
		91-20-3	STEL	15 ppm
	Benzene	71-43-2	TWA	0.5 ppm
		71-43-2	STEL	2.5 ppm
	Pentane	109-66-0	TWA	600 ppm
	Cyclohexane	110-82-7	TWA	100 ppm
	Ethylbenzene	100-41-4	TWA	100 ppm
		100-41-4	STEL	125 ppm
	Heptane [and isomers]	142-82-5	TWA	400 ppm
		142-82-5	STEL	500 ppm

	N-hexane	110-54-3	TWA	50 ppm
Engineering measures	: Use adequate ventilation to keep gas and vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces. Use only intrinsically safe electrical equipment approved for use in classified areas.			
Eye protection	: Safety glasses or goggles are recommended where there is a possibility of splashing or spraying. Ensure that eyewash stations and safety showers are close to the workstation location.			
Hand protection	: Gloves constructed of nitrile or neoprene are recommended. Consult manufacturer specifications for further information.			
Skin and body protection	: If needed to prevent skin contact, chemical protective clothing such as of DuPont TyChem®, Saranex or equivalent recommended based on degree of exposure. Flame resistant clothing such as Nomex ® is recommended in areas where material is stored or handled.			
Respiratory protection	: A NIOSH/ MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Refer to OSHA 29 CFR 1910.134, ANSI Z88.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection selection. Use a NIOSH/ MSHA-approved positive-pressure supplied-air respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.			
Work / Hygiene practices	: Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure. Use good personal hygiene practices. Avoid repeated and/or prolonged skin exposure. Wash hands before eating, drinking, smoking, or using toilet facilities. Do not use as a cleaning solvent on the skin. Do not use solvents or harsh abrasive skin cleaners for washing this product from exposed skin areas. Waterless hand cleaners are effective. Promptly remove contaminated clothing and launder before reuse. Use care when laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Consider the need to discard contaminated leather shoes and gloves.			

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: Clear to straw colored liquid
Odor	: Characteristic hydrocarbon-like
Odor threshold	0.5 - 1.1 ppm
pH	: Not applicable
Melting point/freezing point	About -101°C (-150°F)
Initial boiling point & range	Boiling point varies: 30 – 200°C (85 – 392°F)
Flash point	< -21°C (-5.8°F)
Evaporation rate	: Higher initially and declining as lighter components evaporate
Flammability (solid, gas)	: Flammable vapor released by liquid

Upper explosive limit	7.6 %(V)
Lower explosive limit	1.3 %(V)
Vapor pressure	345 - 1,034 hPa at 37.8 °C (100.0 °F)
Vapor density (air = 1)	Approximately 3 to 4
Relative density (water = 1)	0.8 g/mL
Solubility (in water)	Negligible
Partition coefficient (n-octanol/water)	2 – 7 as log Pow
Auto-ignition temperature	Approximately 250°C (480°F)
Decomposition temperature	Will evaporate or boil and possibly ignite before decomposition occurs.
Kinematic viscosity	0.64 to 0.88 mm ² /s range reported for gasoline
Conductivity (conductivity can be reduced by environmental factors such as a decrease in temperature)	: Hydrocarbon liquids without static dissipater additive may have conductivity below 1 picoSiemens per meter (pS/m). The highest electro-static ignition risks are associated with "ultra-low conductivities" below 5 pS/m. See Section 7 for sources of information on defining safe loading and handling procedures for low conductivity products.

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Vapors may form explosive mixture with air. Hazardous polymerization does not occur.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	Can react with strong oxidizing agents, peroxides, alkaline products and strong acids. Contact with nitric and sulfuric acids will form nitrocresols that can decompose violently.
Conditions to avoid	: Avoid high temperatures, open flames, sparks, welding, smoking and other ignition sources. Avoid static charge accumulation and discharge (see Section 7).
Hazardous decomposition products	: Ignition and burning can release carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

SECTION 11. TOXICOLOGICAL INFORMATION

Skin contact	: Irritating to skin. Can be partially absorbed through skin.
Eye contact	: Irritating to eyes.
Ingestion	: Aspiration hazard if liquid is inhaled into lungs, particularly from vomiting after ingestion. Aspiration may result in chemical pneumonia, severe lung damage, respiratory failure and even death. Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting and diarrhea, and central nervous (brain) effects similar to alcohol intoxication. In severe cases, tremors, convulsions, loss of consciousness, coma, respiratory arrest and death may occur.

Inhalation and further information

Acute toxicity of benzene results primarily from depression of the central nervous system (CNS). Inhalation of concentrations over 50 ppm can produce headache, lassitude, weariness, dizziness, drowsiness, over excitation. Exposure to very high levels can result in unconsciousness and death.

Repeated over-exposure may cause liver and kidney injuries.
Components of the product may affect the nervous system.

IARC has determined that gasoline and gasoline exhaust are possibly carcinogenic in humans. Inhalation exposure to completely vaporized unleaded gasoline caused kidney cancers in male rats and liver tumors in female mice. The U.S. EPA has determined that the male kidney tumors are species-specific and are irrelevant for human health risk assessment. The significance of the tumors seen in female mice is not known. Exposure to light hydrocarbons in the same boiling range as this product has been associated in animal studies with effects to the central and peripheral nervous systems, liver, and kidneys. The significance of these animal models to predict similar human response to gasoline is uncertain. This product contains benzene. Human health studies indicate that prolonged and/or repeated overexposure to benzene may cause damage to the blood-forming system (particularly bone marrow), and serious blood disorders such as aplastic anemia and leukemia. Benzene is listed as a human carcinogen by the NTP, IARC, OSHA and ACGIH.

Component:

Gasoline, natural; Low boiling point naphtha 8006-61-9

Acute oral toxicity: LD50 rat
Dose: 18.8 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 20.7 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation

Eye irritation: Classification: Irritating to eyes.
Result: Moderate eye irritation

Toluene

108-88-3

Acute oral toxicity: LD50 rat
Dose: 636 mg/kg

Acute dermal toxicity: LD50 rabbit
Dose: 12,124 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 49 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation
Prolonged skin contact may defat the skin and produce dermatitis.
Eye irritation: Classification: Irritating to eyes.
Result: Mild eye irritation

Xylene

1330-20-7

Acute oral toxicity: LD50 rat
Dose: 2,840 mg/kg

Acute dermal toxicity: LD50 rabbit
Dose: ca. 4,500 mg/kg

Acute inhalation toxicity: LC50 rat
Dose: 6,350 mg/l
Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.
Result: Mild skin irritation

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation: Classification: Irritating to eyes.

Result: Mild eye irritation

Ethanol; Ethyl alcohol

64-17-5

Acute oral toxicity: LD50 rat

Dose: 6,200 mg/kg

Acute dermal toxicity: LD50 rabbit

Dose: 19,999 mg/kg

Acute inhalation toxicity: LC50 rat

Dose: 8,001 mg/l

Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.

Result: Mild skin irritation

Prolonged skin contact may cause skin irritation and/or dermatitis.

Eye irritation: Classification: Irritating to eyes.

Result: Mild eye irritation

Mild eye irritation

Naphthalene

91-20-3

Acute oral toxicity: LD50 rat

Dose: 2,001 mg/kg

Acute dermal toxicity: LD50 rat

Dose: 2,501 mg/kg

Acute inhalation toxicity: LC50 rat

Dose: 101 mg/l

Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.

Result: Mild skin irritation

Eye irritation: Classification: Irritating to eyes.

Result: Mild eye irritation

Carcinogenicity: N11.00422130

Benzene

71-43-2

Acute oral toxicity: LD50 rat

Dose: 930 mg/kg

Acute inhalation toxicity: LC50 rat

Dose: 44 mg/l

Exposure time: 4 h

Skin irritation: Classification: Irritating to skin.

Result: Mild skin irritation

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation: Classification: Irritating to eyes.

Result: Risk of serious damage to eyes.

Pentane

109-66-0

Acute oral toxicity: LD50 rat

Dose: 2,001 mg/kg

Acute inhalation toxicity: LC50 rat

Dose: 364 mg/l

Exposure time: 4 h

Skin irritation: Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Eye irritation: Classification: Irritating to eyes.

Result: Mild eye irritation

Cyclohexane

110-82-7

Acute dermal toxicity: LD50 rabbit

Dose: 2,001 mg/kg

Acute inhalation toxicity: LC50 rat

Dose: 14 mg/l

Exposure time: 4 h

Ethylbenzene	100-41-4	<u>Skin irritation:</u> Classification: Irritating to skin. Result: Skin irritation
		<u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation
		<u>Acute oral toxicity:</u> LD50 rat Dose: 3,500 mg/kg
Heptane [and isomers]	142-82-5	<u>Acute dermal toxicity:</u> LD50 rabbit Dose: 15,500 mg/kg
		<u>Acute inhalation toxicity:</u> LC50 rat Dose: 18 mg/l Exposure time: 4 h
		<u>Skin irritation:</u> Classification: Irritating to skin. Result: Mild skin irritation
N-hexane	110-54-3	<u>Eye irritation:</u> Classification: Irritating to eyes. Result: Risk of serious damage to eyes.
		<u>Acute oral toxicity:</u> LD50 rat Dose: 15,001 mg/kg
		<u>Acute inhalation toxicity:</u> LC50 rat Dose: 103 g/m3 Exposure time: 4 h
		<u>Skin irritation:</u> Classification: Irritating to skin. Result: Skin irritation Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.
		<u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation
		<u>Acute oral toxicity:</u> LD50 rat Dose: 25,000 mg/kg
		<u>Acute dermal toxicity:</u> LD50 rabbit Dose: 2,001 mg/kg
		<u>Acute inhalation toxicity:</u> LC50 rat Dose: 171.6 mg/l Exposure time: 4 h
		<u>Skin irritation:</u> Classification: Irritating to skin. Result: Skin irritation
		<u>Eye irritation:</u> Classification: Irritating to eyes. Result: Mild eye irritation
		<u>Teratogenicity:</u> N11.00418960

Carcinogenicity

NTP	⋮	Naphthalene (CAS-No.: 91-20-3) Benzene (CAS-No.: 71-43-2)
IARC	⋮	Gasoline, natural; Low boiling point naphtha (CAS-No.: 8006-61-9) Naphthalene (CAS-No.: 91-20-3) Benzene (CAS-No.: 71-43-2) Ethylbenzene (CAS-No.: 100-41-4)
OSHA	⋮	Benzene (CAS-No.: 71-43-2)
CA Prop 65	⋮	WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm. Toluene (CAS-No.: 108-88-3)

Benzene (CAS-No.: 71-43-2)

SECTION 12. ECOLOGICAL INFORMATION

Additional ecological information

: Keep out of sewers, drainage areas, and waterways. Report spills and releases, as applicable, under Federal and State regulations.

Component:

Toluene	108-88-3	<u>Toxicity to fish:</u> LC50 Species: Carassius auratus (goldfish) Dose: 13 mg/l Exposure time: 96 h
		<u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 11,5 mg/l Exposure time: 48 h
		<u>Toxicity to algae:</u> IC50 Species: Selenastrum capricornutum (green algae) Dose: 12 mg/l Exposure time: 72 h
Ethanol; Ethyl alcohol	64-17-5	<u>Toxicity to fish:</u> LC50 Species: Leuciscus idus (Golden orfe) Dose: 8,140 mg/l Exposure time: 48 h
		<u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 9,268 - 14,221 mg/l Exposure time: 48 h
Isopentane; 2-Methylbutane	78-78-4	<u>Toxicity to fish:</u> LC50 Species: Oncorhynchus mykiss (rainbow trout) Dose: 3.1 mg/l Exposure time: 96 h
		<u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 2.3 mg/l Exposure time: 96 h
Naphthalene	91-20-3	<u>Toxicity to algae:</u> EC50 Species: Dose: 33 mg/l Exposure time: 24 h
Pentane	109-66-0	<u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 9.74 mg/l Exposure time: 48 h
Cyclohexane	110-82-7	<u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 3.78 mg/l Exposure time: 48 h

Heptane [and isomers]	142-82-5	<u>Toxicity to fish:</u> LC50 Species: Carassius auratus (goldfish) Dose: 4 mg/l Exposure time: 24 h
		<u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 1.5 mg/l Exposure time: 48 h
N-hexane	110-54-3	<u>Toxicity to fish:</u> LC50 Species: Pimephales promelas (fathead minnow) Dose: 2.5 mg/l Exposure time: 96 h
		<u>Acute and prolonged toxicity for aquatic invertebrates:</u> EC50 Species: Daphnia magna (Water flea) Dose: 2.1 mg/l Exposure time: 48 h

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal : Dispose of container and unused contents in accordance with federal, state and local requirements.

SECTION 14. TRANSPORT INFORMATION**CFR**

Proper shipping name : Petrol
UN-No. : 1203
Class : 3
Packing group : II

TDG

Proper shipping name : Gasoline
UN-No. : UN1203
Class : 3
Packing group : II

IATA Cargo Transport

UN UN-No. : UN1203
Description of the goods : Gasoline
Class : 3
Packaging group : II
ICAO-Labels : 3
Packing instruction (cargo aircraft) : 364
Packing instruction (cargo aircraft) : Y341

IATA Passenger Transport

UN UN-No. : UN1203
Description of the goods : Gasoline
Class : 3

Packaging group : II
ICAO-Labels : 3
Packing instruction : 353
(passenger aircraft)
Packing instruction : Y341
(passenger aircraft)

IMDG-Code

UN-No. : UN 1203
Description of the goods : Gasoline
Class : 3
Packaging group : II
IMDG-Labels : 3
EmS Number : F-E S-E
Marine pollutant : No

SECTION 15. REGULATORY INFORMATION

OSHA Hazards : Flammable liquid
Highly toxic by ingestion
Moderate skin irritant
Severe eye irritant
Carcinogen

TSCA Status : On TSCA Inventory

DSL Status : . All components are on the Canadian DSL list.

SARA 311/312 Hazards : Fire Hazard
Acute Health Hazard
Chronic Health Hazard

CERCLA SECTION 103 and SARA SECTION 304 (RELEASE TO THE ENVIRONMENT)

The CERCLA definition of hazardous substances contains a "petroleum exclusion" clause which exempts crude oil. Fractions of crude oil, and products (both finished and intermediate) from the crude oil refining process and any indigenous components of such from the CERCLA Section 103 reporting requirements. However, other federal reporting requirements, including SARA Section 304, as well as the Clean Water Act may still apply.

California Prop. 65 : WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.

Toluene 108-88-3
Benzene 71-43-2

SECTION 16. OTHER INFORMATION**Further information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Revision Date : 08/09/2012

6, 8, 10, 12, 14, 16, 64, 68, 91, 112, 306, 1092, 1106, 1500, 1570, 1571, 1651, 1652, 1654, 1700, 1701, 1702, 1710, 1711, 1714, 1726, 1729, 1730, 1732, 1733, 1826, 1848, 1880, 1950



SAFETY DATA SHEET

Diesel Fuel

1. IDENTIFICATION

Product Identifier Diesel Fuel

Synonyms: Diesel Fuel, Motor Vehicle Diesel Fuel, Dyed Diesel, * DieselOne®, * DieselOne® w/Platinum Plus DFX, Low Sulfur Diesel (LSD), Ultra Low Sulfur Diesel (ULSD)

Intended use of the product: Fuel

Contact: Global Companies LLC
Water Mill Center
800 South St.
Waltham, MA 02454-9161
www.globalp.com

Contact Information: EMERGENCY TELEPHONE NUMBER (24 hrs): CHEMTREC (800) 424-9300
COMPANY CONTACT (business hours): 800-542-0778

2. HAZARD IDENTIFICATION

According to OSHA 29 CFR 1910.1200 HCS

Classification of the Substance or Mixture

Classification (GHS-US):

Flam. Liquid	Category 3	H226
Skin Corrosion/Irritation	Category 2	H315
Aspiration Hazard	Category 1	H304
STOT SE	Category 3	H336
Carcinogenicity	Category 2	H350
Aquatic Chronic	Category 2	H411
Serious Eye Damage/ Irritation	Category 2B	H319

Labeling Elements



Signal Word (GHS-US):

Hazard Statements (GHS-US):

Danger

H226 – Flammable liquid and vapor.

H315 – Causes Skin irritation.

H304 – May be fatal if swallowed and enters airways.

H336 – May cause drowsiness or dizziness.

H350 – May cause cancer.

H411 – Toxic to aquatic life with long lasting effects.

H319 – May cause eye damage/irritation.

Precautionary Statements (GHS-US):

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P233 - Keep container tightly closed.

P240 – Ground/bond container and receiving equipment.



SAFETY DATA SHEET

Diesel Fuel

P241 – Use explosion-proof electrical/ventilating/lighting equipment pursuant to applicable electrical code.
P242 – Use only non-sparking tools.
P243 – Take precautionary measures against static discharge.
P261 – Avoid breathing dust/fume/gas/mist/vapors/spray.
P264 – Wash skin thoroughly after handling.
P271 – Use only outdoors or in a well-ventilated area.
P273 – Avoid release to the environment.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P303+361+353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse with water/shower.
P308+311 - If exposed or concerned: Get medical advice/attention.
P301+310 - If swallowed: Immediately call a poison center/doctor/...
P331 - Do NOT induce vomiting.
P370+P378 – In case of fire use firefighting foam or other appropriate media for Class B fires to extinguish.
P403+235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 – Dispose of contents/container in accordance with local/regional/national/international regulation.

Other information:

NFPA 704
Health: 1
Fire: 2
Reactivity: 0



3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Composition Information

Mixture

Name	Product Identifier (CAS#)	% (w/w)	Classification
Diesel Fuel	68476-34-6	100	Flam Liq. 3, H226; Skin Irrit. 2, H315; Aspiration 1, H304; STOT SE 3, H336; Carc.2. H350; Aquatic chronic 2, H411
Naphthalene	91-20-3	<0.1	Carc. 2, H351; Acute Tox. 4, H302; Aquatic Acute 1, H400; Aquatic Chronic 1, H410

Additional Formulation Information:

Diesel Fuel consists of C9+ hydrocarbons resulting from distillation of crude oil.

Low Sulfur Diesel Fuel typically contains less than 500 ppm of sulfur

Ultra Low Sulfur Diesel Fuel typically contains less than 15 ppm of sulfur



4. FIRST AID MEASURES

Route	Measures
Inhalation	Remove person to fresh air. If person is not breathing, ensure an open airway and provide artificial respiration. If necessary, provide additional oxygen once breathing is restored if trained to do so. Seek medical attention immediately.
Ingestion	Aspiration Hazard: DO NOT INDUCE VOMITING. Do not give liquids. Obtain immediate medical attention. If spontaneous vomiting occurs, lean victim forward to reduce the risk of aspiration. Ingestion may cause gastrointestinal disturbances including irritation, nausea, vomiting, and diarrhea, and central nervous system (brain) effects similar to alcohol intoxication. In severe cases, tremors, convulsions, loss of consciousness, coma, respiratory failure, and death.
Eye Contact	In case of contact with eyes, immediately flush with clean, low-pressure water for at least 15 min. Hold eyelids open to ensure adequate flushing. Seek medical attention. In case of contact lenses, remove immediately.
Skin Contact	Remove contaminated clothing and shoes. Wash contaminated areas thoroughly with soap and water or waterless hand cleanser. Obtain medical attention if irritation or redness develops. Thermal burns require immediate medical attention depending on the severity and of the area of the body burned.

Most Important Symptoms

Contact with eyes and face may cause irritation. Long-term exposure may cause dermatitis (itching, irritation, pain and swelling).

Inhalation may cause irritation and significant or long term exposure could cause respiratory insufficiency and pulmonary edema.

Ingestion may cause aspiration, gastrointestinal disturbance, and CNS effects.

Immediate Medical Attention and Special Treatment

For contact with skin or eyes, immediately wash or flush contaminated eyes with gently flowing water. If possible, irrigate each eye continuously with 0.9% saline (NS). If ingested, rinse mouth. Do NOT induce vomiting, as this may cause chemical pneumonia (fluid in the lungs).

If inhaled, administer oxygen or establish a patent airway if breathing is labored. Suction if necessary. Monitor closely, anticipate seizures. Consider orotracheal or nostracheal intubation of airway control if patient is unconscious or is in severe respiratory distress.

Discard any clothing or shoes contaminated as they may be flammable.

5. FIRE-FIGHTING MEASURES

Extinguishing Media

Foam, carbon dioxide, dry chemical are most suitable

SMALL FIRES: Any extinguisher suitable for Class B fires, dry chemical, CO₂, water spray, firefighting foam, or Halon. Small fires in the incipient (beginning) stage may typically be extinguished using handheld portable fire extinguishers and other firefighting equipment.

LARGE FIRES: Foam, carbon dioxide, dry chemical. Water may be ineffective for fighting the fire, but may be used to cool fire-exposed containers.

Specific Hazards / Products of Combustion

Moderate fire hazard when exposed to heat or flame with a very low flash point. Product is flammable and easily ignited when exposed to heat, spark, open flame or other source of ignition. Flowing product may be ignited by self-generated static electricity. When mixed with air and exposed to an ignition source, flammable vapors can burn in the open or explode in confined spaces. Being heavier than air, vapors may travel long distances to an ignition source and flash back. Runoff to sewer may cause fire or explosion hazard.

Combustion may produce smoke, carbon monoxide and other products of incomplete combustion.

Special Precautions and Protective Equipment for Firefighters

Isolate area around container involved in fire. Cool tanks, shells, and containers exposed to fire and excessive heat with water.



SAFETY DATA SHEET

Diesel Fuel

For massive fires the use of unmanned hose holders or monitor nozzles may be advantageous to further minimize personnel exposure. Major fires may require withdrawal, allowing the tank to burn. Large storage tank fires typically require specially trained personnel and equipment to extinguish the fire, often including the need for properly applied firefighting foam.

Fighting Equipment/Instructions

Firefighting activities that may result in potential exposure to high heat, smoke or toxic by-products of combustion should require NIOSH- approved pressure-demand self-contained breathing apparatus with full face piece and protective clothing.

Refer to Section 9 for fire properties of this chemical including flash point, auto ignition temperature, and explosive limits.

6. ACCIDENTAL RELEASE MEASURES

ACTIVATE FACILITY SPCC, SPILL CONTINGENCY or EMERGENCY PLAN.

Personal Precautions

Due to high vapor density, flammable / toxic vapors may be present in low lying areas, dikes, pits, drains, or trenches. Vapors may accumulate in low lying areas and reach ignitable concentrations. Ventilate the area. Use of non-sparking tools and intrinsically safe equipment is recommended. Potential for flammable atmosphere should be monitored using a combustible gas indicator positioned downwind of the spill area. Refer to Sections 2 and 7 for further hazard warnings and handling instructions.

Use appropriate personal protective equipment to prevent eye/skin contact and absorption. Use NIOSH approved respiratory protection, if warranted, to prevent exposures above permissible limits. Refer to Section 8. Contaminated clothing should not be near sources of ignition.

Emergency Measures

As an immediate precautionary measure, isolate spill or leak area for at least 50 meters (150 feet) in all directions. Consider wind direction. Secure all ignition sources (flame, spark, hot work, hot metal, etc.) from area. Evaluate the direction of product travel, diking sewers, etc. to confirm spill areas. Do not touch or walk-through spilled material. For large spills, isolate initial action distance downwind 1,000 ft. (300 m).

Environmental Precautions

Stop the spill to prevent environmental release if it can be done safely. Product is toxic to aquatic life. Take action to isolate environmental receptors including drains, storm sewers and natural water bodies. Keep on impervious surface if at all possible. Use water sparingly to prevent product from spreading. Foam and absorbents may be used to reduce / prevent airborne release.

Spills may infiltrate subsurface soil and groundwater; professional assistance may be necessary to determine the extent of subsurface impact.

Follow federal, state or local requirements for reporting environmental release where necessary. Refer to Section 15 for further information.

Containment and Clean-Up Methods

Carefully contain and stop the source of the spill, if safe to do so. Protect bodies of water by diking absorbents, or absorbent boom, if possible. Do not flush down sewer or drainage systems, unless system is designed and permitted to handle such material. The use of firefighting foam may be useful in certain situations to reduce vapors. The proper use of water spray may effectively disperse product vapors or the liquid itself, preventing contact with ignition sources or areas/equipment that require protection.

Take up with dry earth, sand or other non-combustible, inert oil absorbing materials. Carefully shovel, scoop or sweep up into a waste container with clean, non-sparking tools for reclamation or disposal. Response and cleanup crews must be properly trained and must utilize proper protective equipment. Refer to Section 8 for appropriate protective equipment.

7. HANDLING AND STORAGE

USE ONLY AS A FUEL.

DO NOT SIPHON BY MOUTH.

Handling Precautions

Handle as a flammable liquid. Keep away from heat, sparks, and open flame. No smoking. Electrical equipment should be approved for classified area. Bond and ground containers during product transfer pursuant to NFPA 70 and API RP 2003 to



SAFETY DATA SHEET

Diesel Fuel

reduce the possibility of static-initiated fire or explosion. Follow precautions to prevent static initiated fire.

Use good personal hygiene practices. Use only with protective equipment specified in Section 8. Avoid repeated and/or prolonged skin exposure. Use only outdoors or in well ventilated areas. Wash hands before eating, drinking, smoking, or using toilet facilities. Do not use as a cleaning solvent on the skin. Do not use solvents or harsh abrasive skin cleaners for washing this product from exposed skin areas. Waterless hand cleaners are effective. Promptly remove contaminated clothing and launder before reuse. Use care when laundering to prevent the formation of flammable vapors which could ignite via washer or dryer. Consider the need to discard contaminated leather shoes and gloves. Emergency eye wash capability should be available in the near proximity to operations presenting a potential splash exposure.

Special slow load procedures for "switch loading" must be followed to avoid the static ignition hazard that can exist when higher flash point material (such as fuel oil) is loaded into tanks previously containing low flash point products (such as this product) - see API RP 2003, "Protection Against Ignitions Arising Out Of Static, Lightning and Stray Currents."

Storage

Large quantities of diesel fuel are stored in tanks or portable containers at an ambient storage temperature. Separate from incompatible chemicals (Refer to Section 10) by distance or secondary containment. Keep away from flame, sparks, excessive temperatures and open flame. Use approved vented containers that are clearly labeled. Label all secondary containers that this material is transferred into with the chemical name and associated hazard(s). Empty product containers or vessels may contain flammable vapors. Do not pressurize, cut, heat, weld or expose such containers to sources of ignition.

Storage tanks should have a venting system. If stored in small containers, the area should be well ventilated, away from ignition sources and protected from potential damage or vehicular traffic. Post "No Smoking" signs in product storage areas. This storage area should comply with NFPA 30 "Flammable and Combustible Liquid Code" or applicable building code. The cleaning of tanks previously containing this product should follow API Recommended Practice (RP) 2013 "Cleaning Mobile Tanks in Flammable and Combustible Liquid Service" and API RP 2015 "Safe Entry and Cleaning of Petroleum Storage Tanks".

Incompatibles

Keep away from strong oxidizers, ignition sources and heat.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Occupational Exposure Limits

Component	CAS #	List	Value
Diesel Fuel	68476-34-6	ACGIH TLV-TWA	100 mg/m ³ *
Naphthalene	91-20-3	ACGIH TLV-TWA OSHA PEL ACGIH STEL	10 ppm 10 ppm 15 ppm

*Critical effects; Skin; A3; CNS impairment.

Engineering Controls

Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces. Intrinsically safe equipment and non-sparking tools shall be used in circumstances where concentrations may exceed lower flammable limits. Grounding and bonding shall be used to prevent accumulation and discharge of static electricity. Emergency shower and eyewash should be provided in proximity to handling areas in the event of exposure to decontaminate.

Personal Protective Equipment

Exposure	Equipment
Eye / Face	Wear appropriate chemical protective glasses or goggles or face shields to prevent skin and eye contact especially caused from splashing.
Skin	Wear appropriate personal protective clothing to prevent skin contact. Gloves constructed of nitrile, neoprene or PVC are recommended when handling this material. Chemical protective clothing such as of E.I. DuPont TyChem®, Saranex® or equivalent recommended based on degree of exposure. Note: The resistance of specific material may vary from product to product as well as with degree of exposure.



SAFETY DATA SHEET

Diesel Fuel

Exposure	Equipment
Respiratory	<p>A NIOSH/MSHA-approved air-purifying respirator with organic vapor cartridges or canister may be permissible under certain circumstances where airborne concentrations are or may be expected to exceed exposure limits or for odor or irritation. Protection provided by air-purifying respirators is limited. Refer to OSHA 29 CFR 1910.134, ANSI Z88.2-1992, NIOSH Respirator Decision Logic, and the manufacturer for additional guidance on respiratory protection selection and limitations.</p> <p>Use a positive pressure, air-supplied respirator if there is a potential for uncontrolled release, exposure levels are not known, in oxygen-deficient atmospheres, or any other circumstance where an air-purifying respirator may not provide adequate protection.</p>
Thermal	<p>Product is stored at ambient temperature. No thermal protection is required except for emergency operations involving actual or potential for fire. Use adequate ventilation to keep vapor concentrations of this product below occupational exposure and flammability limits, particularly in confined spaces.</p>

9. PHYSICAL AND CHEMICAL PROPERTIES

Property	Value
Appearance	Clear or straw-colored liquid. May be dyed red for distribution.
Odor	Mild characteristic petroleum distillate odor.
Odor Threshold	<1 ppm
pH	Not available
Melting Point	-22 to -0.4 °F (-30 to -18 °C)
Boiling Point Range	320 to 690 °F (160 to 366 °C)
Flash Point	> 125.6 °F (52 °C) PMCC
Evaporation Rate	Slow, varies with conditions
Flammability	Flammable liquid
Flammable Limits	0.6 % - 6.5%
Vapor Pressure	0.009 psia @ 70 °F
Vapor Density	> 1 (air=1)
Specific Gravity	0.83-0.86 @ 60 °F (16 °C) (water=1)
Solubility	Insoluble in water; miscible with other petroleum solvents.
Partition Coefficient (N-octanol/water)	Log Kow range of 3.3 to >6.0
Autoignition Temperature	494 °F (257 °C)
Decomposition Temperature	When heated it emits acrid smoke and irritating vapors.
Viscosity	>3 cSt
Percent Volatiles	100

10. STABILITY AND REACTIVITY

Stability

This is a stable material that is flammable liquid (OSHA/GHS hazard category 3). Stable during transport.

Reactivity

Material is not self-reacting. Flammable concentrations may be present in air. Compound can react with oxidizing materials.



Possibility of Hazardous Reactions

Hazardous polymerization will not occur.

Incompatibility

Keep away from strong oxidizers such as nitric and sulfuric acids.

Conditions to Avoid

Avoid high temperatures, open flames, sparks, static electricity, welding, smoking and other ignition sources.

Hazardous Decomposition Products

Carbon monoxide, carbon dioxide and non-combusted hydrocarbons (smoke).

11. TOXICOLOGICAL INFORMATION

Acute Toxicity:

Acute Toxicity (Inhalation LC50)

Diesel Fuel (68476-34-6)

LC50 Inhalation Rat >6 mg/l/4h

Acute Toxicity (Dermal LD50)

Diesel Fuel (68476-34-6)

LD50 Dermal Rabbit >5000 mg/kg

Acute Toxicity (Oral LD50)

Diesel Fuel (68476-34-6)

LD50 Oral Rabbit >5000 mg/kg

Skin Corrosion/Irritation: Prolonged and repeated contact may cause skin irritation leading to dermatitis. Liquid may be absorbed through the skin in toxic amounts if large areas of skin are exposed repeatedly.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available

Carcinogenicity: OSHA: NO, IARC: Group 3, NTP: NO, ACGIH: NOIC:A3, NIOSH: NO

IARC: Group 3 – Not classifiable as to their carcinogenicity to humans

ACGIH: A3 – Confirmed animal carcinogen with unknown relevance to humans.

Studies have shown that similar products produce skin tumors in laboratory animals following repeated applications without washing or removal. The significance of this finding to human exposure has not been determined. Other studies with active skin carcinogens have shown that washing the animal's skin with soap and water between applications reduced tumor formation.

IARC classifies whole diesel fuel exhaust particulates (byproduct of combustion of this material) carcinogenic to humans (Group 1) and NIOSH regards diesel fuel exhaust particulate as a potential occupational carcinogen.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Specific Target Organ Toxicity (Single Exposure): Inhalation exposure may cause drowsiness or dizziness by inhalation exposure.

Aspiration Hazard: The major health threat of ingestion occurs from the danger of aspiration (breathing) of liquid drops into the lungs, particularly from vomiting. Aspiration may result in chemical pneumonia (fluid in the lungs), severe lung damage, respiratory failure and even death.

Potential Health Effects: Vapor irritating to skin, eyes, nose, and throat. Ingestion may cause gastrointestinal disturbances, including irritation, nausea, vomiting and diarrhea, and central nervous system (brain) effects similar to alcohol intoxication. In severe cases, tremors, convulsions, loss of consciousness, coma, respiratory arrest, and death may occur.

WARNING: The burning of any hydrocarbon as a fuel in an area without adequate ventilation may result in hazardous levels of



SAFETY DATA SHEET

Diesel Fuel

combustion products, including carbon monoxide, and inadequate oxygen levels, which may cause unconsciousness, suffocation, and death.

12. ECOLOGICAL INFORMATION

Toxicity:

This material is expected to be toxic to aquatic organisms and may cause long-term adverse effects in the aquatic environment.

Data for Component: Diesel Fuel (68476-34-6)

Material is toxic to aquatic organisms based on an acute basis (LC50/EC50 >1 but \leq 10 mg/L in the most sensitive species tested).

Material is a long-term aquatic hazard based on a chronic basis (LC50/EC50 >1 but \leq 10 mg/L in the most sensitive species tested).

Persistence and Degradation: This material is not expected to be readily biodegradable.

Bioaccumulative Potential: Not available

Mobility in Soil: Not available

Other Adverse Effects: None known

Other Information: Avoid release to the environment.

13. DISPOSAL CONSIDERATIONS

Consult federal, state and local waste regulations to determine appropriate disposal options. May be considered a hazardous waste if disposed. Direct solid waste (landfill) or incineration at a solid waste facility is not permissible. Do not discharge to sanitary or storm sewer. Personnel handling waste containers should follow precautions provided in this document.

Shipping containers must be DOT authorized packages. Follow licensure and regulations for transport of hazardous material and hazardous waste as applicable.

14. TRANSPORT INFORMATION

US DOT

UN Identification Number	NA 1993 / UN 1202
Proper Shipping Name	Diesel Fuel
Hazard Class and Packing Group	3, PGIII
Shipping Label	Combustible liquid
Placard / Bulk Package	Combustible liquid, 1993
Emergency Response Guidebook Guide Number	128

IATA Information

UN Identification Number	UN 1202
Proper Shipping Name	Combustible-Liquid, N.O.S. (Fuel, Diesel)
Hazard Class and Packing Group	3, PGIII
ICAO Label	3
Packing Instructions Cargo	310
Max Quantity Per Package Cargo	220L
Packing Instructions Passenger	309Y
Max Quantity per Package	60L

ICAO

UN Identification Number	UN 1202
Shipping Name / Description	Combustible-Liquid, N.O.S. (Fuel, Diesel)
Hazard Class and Packing Group	3, PG III
IMDG Label	3



SAFETY DATA SHEET

Diesel Fuel

IMDG

UN Identification Number	UN 1202
Shipping Name / Description	Combustible-Liquid, N.O.S. (Fuel, Diesel)
Hazard Class and Packing Group	3, PGIII
IMDG Label	3
EmS Number	F-E-S-E
Marine Pollutant	Yes

15. REGULATORY INFORMATION

U.S. Federal, State, and Local Regulatory Information

Any spill or uncontrolled release of this product, including any substantial threat of release, may be subject to federal, state and/or local reporting requirements. This product and/or its constituents may also be subject to other federal, state, or local regulations; consult those regulations applicable to your facility/operation.

OSHA Hazard Communication Standard

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Superfund Amendments and Reauthorization Act of 1986 Title III (Emergency Planning And Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard	Yes
Delayed (Chronic) Health Hazard	Yes
Fire Hazard	Yes
Reactive Hazard	No
Sudden Release of Pressure Hazard	No

Clean Water Act (Oil Spills)

Any spill or release of this product to "navigable waters" (Essentially any surface water, including certain wetlands) or adjoining shorelines sufficient to cause a visible sheen or deposit of a sludge or emulsion must be reported immediately to the National Response Center (1-800-424-8802) or, if not practical, the U.S. Coast Guard with follow up to the National Response Center, as required by U.S. Federal Law. Also contact appropriate state and local regulatory agencies as required.

CERCLA Section 103 and SARA Section 304 (Release to the Environment)

The CERCLA definition of hazardous substances contains a "petroleum exclusion" clause which exempts this material. This product does not contain any chemicals subject to the reporting requirements of CERCLA Section 103 or SARA 304.

SARA Section 313- Supplier Notification

This product does not contain any chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act (EPCRA) of 1986 and of 40 CFR 372.

EPA Notification (Oil Spills)

If there is a discharge of more than 1,000-gallons of oil into or upon navigable waters of the United States, or if it is the second spill event of 42 gallons or more of oil into water within a twelve (12) month period, a written report must be submitted to the Regional Administrator of the EPA within sixty days of the event.

Pennsylvania Right to Know Hazardous Substance list:

The following product components are cited in the Pennsylvania Special Hazardous Substance List, and are present at levels which require reporting.

Component	CAS	Amount
Diesel Fuel	68476-34-6	100%

New Jersey Right to Know Hazardous Substance list:

The following product components are cited in the New Jersey Right to Know Hazardous Substance List, and are present at levels which require reporting.

Component	CAS	Amount
Diesel Fuel	68476-34-6	100%



SAFETY DATA SHEET

Diesel Fuel

California Proposition 65 WARNING: This product contains chemicals known to the State of California to cause Cancer or Reproductive Toxicity.

Component	CAS	Amount
Naphthalene	91-20-3	<0.1%

U.S. Toxic Substances Control Act

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

CEPA - Domestic Substances List (DSL)

All substances contained in this product are listed on the Canadian Domestic Substances List (DSL) or are not required to be listed.

Canadian Regulatory Information (WHMIS)

Class B3 – Combustible Liquid

Class D2A – Materials causing other toxic effects. (Very Toxic)

16. OTHER INFORMATION

Version	4
Issue Date	May 20, 2016
Prior Issue Date	May 3, 2015

Description of Revisions

Revised to meet Globally Harmonized System for chemical hazard communication requirements pursuant to OSHA regulatory revisions 77 FR 17884, March 26, 2012.

Abbreviations

°F	Degrees Fahrenheit (temperature)	mL	Milliliter
<	Less than	mm ²	Square millimeters
=	Equal to	mmHg	Millimeters of mercury (pressure)
>	Greater than	N/A	Not applicable
AP	Approximately	N/D	Not determined
C	Centigrade (temperature)	ppm	Parts per million
kg	Kilogram	sec	Second
L	Liter	ug	Micrograms
mg	Milligrams		

Acronyms

ACGIH	American Conference of Governmental Industrial Hygienists	GHS	Global Harmonized System
AIHA	American Industrial Hygiene Association	HMIS	Hazardous Materials Information System
AL	Action Level	IARC	International Agency for Research On Cancer
ANSI	American National Standards Institute	IATA	International Air Transport Association
API	American Petroleum Institute	IMDG	International Maritime Dangerous Goods
CAS	Chemical Abstract Service	Koc	Soil Organic Carbon
CERCLA	Comprehensive Emergency Response, Compensation, and Liability Act	LC50	Lethal concentration 50%
DOT	U.S. Department of Transportation	LD50	Lethal dose 50%
EC50	Ecological concentration 50%	MSHA	Mine Safety and Health Administration
EPA	U.S. Environmental Protection Agency	NFPA	National Fire Protection Association
ERPG	Emergency Response Planning Guideline	NIOSH	National Institute of Occupational Safety and Health
		NOIC	Notice of Intended Change



SAFETY DATA SHEET

Diesel Fuel

NTP	National Toxicology Program	STEL	Short Term Exposure Limit (generally 15 minutes)
OPA	Oil Pollution Act of 1990	TLV	Threshold Limit Value (ACGIH)
OSHA	U.S. Occupational Safety & Health Administration	TSCA	Toxic Substances Control Act
PEL	Permissible Exposure Limit (OSHA)	TWA	Time Weighted Average (8 hr.)
RCRA	Resource Conservation and Recovery Act Reauthorization Act of 1986 Title III	UN	United Nations
REL	Recommended Exposure Limit (NIOSH)	UNECE	United Nations Economic Commission for Europe
RVP	Reid Vapor Pressure	WEEL	Workplace Environmental Exposure Level (AIHA)
SARA	Superfund Amendments and	WHMIS	Canadian Workplace Hazardous Materials Information System
SCBA	Self Contained Breathing Apparatus		
SPCC	Spill Prevention, Control, and Countermeasures		

Disclaimer of Expressed and Implied Warranties

Information presented herein has been compiled from sources considered to be dependable, and is accurate and reliable to the best of our knowledge and belief, but is not guaranteed to be so. Since conditions of use are beyond our control, we make no warranties, expressed or implied, except those that may be contained in our written contract of sale or acknowledgment.

Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Additionally, vendor assumes no responsibility for injury to vendee or third persons proximately caused by abnormal use of the material, even if reasonable safety procedures are followed. Furthermore, vendee assumes the risk in their use of the material.

**** End of Safety Data Sheet ****

Splash Windshield Washer Fluid MSDS Sheets

- **Splash +32° F**
- **Splash +22° F**
- **Splash -20° F**
- **Splash -25° F**

Splash +32° F MSDS Sheets

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: +32°F SPLASH WINDSHIELD WASH

SECTION 1 - MANUFACTURER'S INFORMATION

Manufacturer: SuperClean Brands, Inc.
51 East Maryland Avenue
St. Paul, MN 55117-4615

Telephone: (651) 489-8211

Facsimile: (651) 489-8247

Transportation Emergency (for immediate information about a chemical or to seek assistance from a manufacturer): 1-800-535-5053

Date Updated: June 26, 2009

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Common Name: Windshield Washer Fluid

Product Use: Used for cleaning windshields

Product Identification: Windshield Washer Fluid

NFPA HAZARD RATINGS

HEALTH - 1

FLAMMABILITY - 2

REACTIVITY - 0

OTHER - NOT APPLICABLE

Hazardous Component*	Approximate Composition	OSHA Permissible Exposure Limit**	NIOSH REL	ACGIH Threshold Limit Value	IDLH (NIOSH)
Methanol (Methyl Alcohol) -CAS 67-56-1 -UN 1230 (DOT Guide 28)	<1 percent by weight	200 ppm (260 mg/m ³) 8-Hour TWA (Skin)	200 ppm (260 mg/m ³) 8-Hour TWA 250 ppm (310 mg/m ³) Ceiling (Skin)	200 ppm (260 mg/m ³) 8-Hour TWA 250 ppm (310 mg/m ³) Short-term Exposure Limit (15-minute TWA) (Skin)	6,000 ppm (0.6 percent in air)

* The hazardous component listed is not a known or suspected human carcinogen as listed or determined by the National Agency for Research on Cancer, National Toxicological Program "NTP Seventh Annual Report on Carcinogens," or International Agency for Research on Cancer (IARC) monograph reviews. In addition, it is not considered a carcinogen by the Occupational Safety and Health Administration or the National Institute for Occupational Safety and Health.

** This MSDS contains the 1989 PEL's and from the June 1993 Air Contaminants Final Rule, specified in Tables Z-1, Z-2, and Z-3 [Federal Register; 58(124):35338-35351; June 30, 1993].

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: +32°F SPLASH WINDSHIELD WASH

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 200°F (for product)

Flash Point: 200F

Solubility in Water: Soluble

Vapor Pressure: 20mm @ 90° (methanol)

Vapor Density: 1.11 (methanol)

Ionization Potential: 10.84 eV (methanol)

Freezing Point: +32°F

Appearance and Odor: The windshield washer is blue, and it has a mild characteristic pungent odor from the methanol. The odor threshold for methanol is 10 ppm.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flammable Limits: UEL - 36 percent for methanol LEL - 6 percent for methanol

Autoignition Temperature: 878°F for methanol

Extinguishing Media for Methanol

Small Fires: Dry chemical, carbon dioxide, water spray or alcohol resistant foam.

Large Fires: Water spray, fog or alcohol-resistant foam.

Special Fire Fighting Procedures: Move container away from fire area if you can do so without risk. Dike fire control water for later disposal; do not scatter the material. Apply cooling water to the sides of containers exposed to flames until well after the fire is out.

Unusual Fire and Explosion Hazards for Methanol: Flammable/combustible material; may be ignited by heat, spark or flame. Vapors may travel to a source of ignition and flash back. Container may explode in heat of fire. Vapor explosion and poison hazard indoors, outdoors, or in sewers. Runoff to sewer may create fire or explosion hazard.

SECTION 5 - REACTIVITY DATA

Stability/Polymerization: In a closed container, methyl alcohol is stable at room temperature and it is stable under routine handling and storage. Hazardous polymerization will not occur.

Incompatibility (Material to Avoid): Incompatible with beryllium dihydride; metals; oxidants; potassium tert-butoxide; carbon tetrachloride + metals; dichloromethane. Can react vigorously with oxidizing materials.

Explosive reaction with chloroform + sodium methoxide; diethyl zinc. Violent reaction with alkyl aluminum salts; acetylene bromide; chloroform + sodium hydroxide; CrO_3 ; cyanuric chloride; (I + ethanol + HgO); $\text{Pb}(\text{ClO}_4)_2$; HClO_4 ; P_2O_5 ; ($\text{KOH} + \text{CHCl}_3$); nitric acid¹

Hazardous Decomposition or By-products: When methanol is heated to decomposition, carbon dioxide and carbon monoxide may be produced, as well as formaldehyde may be produced, and it emits acrid smoke and irritating fumes.

¹Lewis, Richard J., Sr.: *Sax's Dangerous Properties of Industrial Materials, Eighth Edition*. New York, New York: Van Nostrand Reinhold, 1992.

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: +32°F SPLASH WINDSHIELD WASH

SECTION 6 - HEALTH HAZARD DATA

Routes of Entry (Methanol): The primary routes of entry are inhalation, ingestion, and absorption.

Health Hazards and Signs and Symptoms of Exposure (Methanol): Irritant to eyes, skin, and upper respiratory system. Headaches, drowsiness, dizziness, vertigo, light-headed, nausea, and vomiting. Visual disturbance, optic nerve damage, and blindness. Skin exposure hazard.

Target Organs: Central nervous system, digestive tract, eyes, and skin.

Acute Effects: Eye irritation. Inhalation can result nose irritation, headache, fatigue, nausea, visual impairment or complete and possible blindness, acidosis, convulsions, circulatory collapse, respiratory fatigue, and death. Ingestion can cause gastrointestinal (GI) irritation followed by the symptoms described for inhalation and possible kidney impairment. Skin contact results in a cold sensation, dryness, and cracking, possibly leading to dermatitis. Methyl alcohol may be absorbed through the skin and may cause headache, fatigue, and visual disturbances. Eye contact results in irritation with lacrimation, inflamed lids, and photophobia.

Chronic Effects: Chronic exposure may result in visual impairment or blindness.

Medical Conditions Generally Aggravated by Exposure: Ocular, respiratory, or dermal disorders may be aggravated by methanol exposure.

Emergency and First Aid Procedures:

Eyes:	Rinse with water 15 to 20 minutes, seek medical assistance.
Skin:	Flush with water for 15 minutes.
Inhalation:	Remove from source to fresh air, provide respiratory support as needed.
Ingestion:	Call Physician, hospital emergency room or Poison Control Center immediately.

GET PROMPT MEDICAL ATTENTION

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING

Steps to be Taken in Case Material is Released or Spilled:

- Keep unnecessary people away; isolate hazard area and deny entry.
- Stay upwind; keep out of low areas.
- Shut off ignition sources; no flares, smoking or flames in hazard area.
- Positive pressure self-contained breathing apparatus and chemical protective clothing is recommended for personnel involved in clean-up procedures with no fire.
- Do not walk through spilled material; stop leak if it can be done without risk.
- Water spray may reduce vapor; but it will not prevent ignition in closed spaces.

Waste Disposal Method: Dispose of in accordance with federal, state and local regulations.

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: +32°F SPLASH WINDSHIELD WASH

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Under normal use conditions (outdoor windshield cleaning), respiratory protection is not justified.

Protective Eye Wear: Splash goggles are recommended when handling the solution. Contact lens use is not recommended.

Protective Clothing: The selection of protective clothing and gloves is dependent upon anticipated exposure. As reported by the manufacturer, Best Glove style 725R (PVC) offers excellent protection for up to 240 minutes of complete immersion.

SECTION 9 - OTHER HAZARDOUS INFORMATION AND DEFINITIONS

OSHA PEL: The Occupational Safety and Health Administration's Permissible Exposure Limit, which is defined as the maximum concentration of contaminant to which a normal healthy individual may be exposed 8-hours per day, 40-hours per week, without experiencing adverse health effects over a working lifetime.

ACGIH TLV: American Conference of Governmental Industrial Hygienist's Threshold Limit Value, similar to the OSHA PEL but not considered a legal standard.

SECTION 10 – TRANSPORTATION INFORMATION

DOT Designation:

Not Regulated

MSDS Prepared by: Maxim Technologies, Inc.

Judgements as to the suitability herein for the user's purposes are necessarily the user's responsibility. Therefore, although reasonable care has been taken in the preparation of such information, Maxim Technologies, Inc., extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the intended purposes or for the consequences of its use.

Splash +22° F MSDS Sheets

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: +22° F Splash Windshield Washer Fluid

SECTION 1 - MANUFACTURER'S INFORMATION

Manufacturer: SuperClean Brands, Inc.
51 East Maryland Avenue
St. Paul, MN 55117-4615

Telephone: (651) 489-8211

Facsimile: (651) 489-8247

Transportation Emergency (for immediate information about a chemical or to seek assistance from a manufacturer): 1-800-535-5053

Date Updated: December 12, 2007

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Common Name: Windshield Washer Fluid

Product Use: Used for cleaning windshields

Product Identification: Windshield Washer Fluid

NFPA HAZARD RATINGS
HEALTH - 1
FLAMMABILITY - 2
REACTIVITY - 0
OTHER - NOT APPLICABLE

Hazardous Component*	Approximate Composition	OSHA Permissible Exposure Limit**	NIOSH REL	ACGIH Threshold Limit Value	IDLH (NIOSH)
Methanol (Methyl Alcohol) -CAS 67-56-1 -UN 1230 (DOT Guide 28)	< 10 by weight	200 ppm (260 mg/m ³) 8-Hour TWA (Skin)	200 ppm (260 mg/m ³) 8-Hour TWA 250 ppm (310 mg/m ³) Ceiling (Skin)	200 ppm (260 mg/m ³) 8-Hour TWA 250 ppm (310 mg/m ³) Short-term Exposure Limit (15-minute TWA) (Skin)	6,000 ppm (0.6 percent in air)

* The hazardous component listed is not a known or suspected human carcinogen as listed or determined by the National Agency for Research on Cancer, National Toxicological Program "NTP Seventh Annual Report on Carcinogens," or International Agency for Research on Cancer (IARC) monograph reviews. In addition, it is not considered a carcinogen by the Occupational Safety and Health Administration or the National Institute for Occupational Safety and Health.

** This MSDS contains the 1989 PEL's and from the June 1993 Air Contaminants Final Rule, specified in Tables Z-1, Z-2, and Z-3 [Federal Register; 58(124):35338-35351; June 30, 1993].

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: +22° F Windshield Washer Fluid

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 200°F (for product)

Flash Point: 150°F

Solubility in Water: Soluble

Vapor Density: 1.11 (methanol)

Vapor Pressure: 100mm @ 21.2°F (methanol)

Freezing Point: +22°F

Ionization Potential: 10.84 eV (methanol)

Appearance and Odor: The windshield washer is blue, and it has a mild characteristic pungent odor from the methanol. The odor threshold for methanol is 10 ppm.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flammable Limits: UEL - 36 percent for methanol LEL - 6 percent for methanol

Autoignition Temperature: 878°F for methanol

Extinguishing Media for Methanol

Small Fires: Dry chemical, carbon dioxide, water spray or alcohol resistant foam.

Large Fires: Water spray, fog or alcohol-resistant foam.

Special Fire Fighting Procedures: Move container away from fire area if you can do so without risk. Dike fire control water for later disposal; do not scatter the material. Apply cooling water to the sides of containers exposed to flames until well after the fire is out.

Unusual Fire and Explosion Hazards for Methanol: Flammable/combustible material; may be ignited by heat, spark or flame. Vapors may travel to a source of ignition and flash back. Container may explode in heat of fire. Vapor explosion and poison hazard indoors, outdoors, or in sewers. Runoff to sewer may create fire or explosion hazard.

SECTION 5 - REACTIVITY DATA

Stability/Polymerization: In a closed container, methyl alcohol is stable at room temperature and it is stable under routine handling and storage. Hazardous polymerization will not occur.

Incompatibility (Material to Avoid): Incompatible with beryllium dihydride; metals; oxidants; potassium tert-butoxide; carbon tetrachloride + metals; dichloromethane. Can react vigorously with oxidizing materials.

Explosive reaction with chloroform + sodium methoxide; diethyl zinc. Violent reaction with alkyl aluminum salts; acetylene bromide; chloroform + sodium hydroxide; CrO₃; cyanuric chloride; (I + ethanol + HgO); Pb(ClO₄)₂; HClO₄; P₂O₃; (KOH + CHCl₃); nitric acid¹

Hazardous Decomposition or By-products: When methanol is heated to decomposition, carbon dioxide and carbon monoxide may be produced, as well as formaldehyde may be produced, and it emits acrid smoke and irritating fumes.

¹Lewis, Richard J., Sr.: *Sax's Dangerous Properties of Industrial Materials, Eighth Edition*. New York, New York: Van Nostrand Reinhold, 1992.

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: +22° F Windshield Washer Fluid

SECTION 6 - HEALTH HAZARD DATA

Routes of Entry (Methanol): The primary routes of entry are inhalation, ingestion, and absorption.

Health Hazards and Signs and Symptoms of Exposure (Methanol): Irritant to eyes, skin, and upper respiratory system. Headaches, drowsiness, dizziness, vertigo, light-headed, nausea, and vomiting. Visual disturbance, optic nerve damage, and blindness. Skin exposure hazard.

Target Organs: Central nervous system, digestive tract, eyes, and skin.

Acute Effects: Eye irritation. Inhalation can result nose irritation, headache, fatigue, nausea, visual impairment or complete and possible blindness, acidosis, convulsions, circulatory collapse, respiratory fatigue, and death. Ingestion can cause gastrointestinal (GI) irritation followed by the symptoms described for inhalation and possible kidney impairment. Skin contact results in a cold sensation, dryness, and cracking, possibly leading to dermatitis. Methyl alcohol may be absorbed through the skin and may cause headache, fatigue, and visual disturbances. Eye contact results in irritation with lacrimation, inflamed lids, and photophobia.

Chronic Effects: Chronic exposure may result in visual impairment or blindness.

Medical Conditions Generally Aggravated by Exposure: Ocular, respiratory, or dermal disorders may be aggravated by methanol exposure.

Emergency and First Aid Procedures:

Eyes:	Rinse with water 15 to 20 minutes, seek medical assistance.
Skin:	Flush with water for 15 minutes.
Inhalation:	Remove from source to fresh air, provide respiratory support as needed.
Ingestion:	Call Physician, hospital emergency room or Poison Control Center immediately.

GET PROMPT MEDICAL ATTENTION

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in Case Material is Released or Spilled:

- Keep unnecessary people away; isolate hazard area and deny entry.
- Stay upwind; keep out of low areas.
- Shut off ignition sources; no flares, smoking or flames in hazard area.
- Positive pressure self-contained breathing apparatus and chemical protective clothing is recommended for personnel involved in clean-up procedures with no fire.
- Do not walk through spilled material; stop leak if it can be done without risk.
- Water spray may reduce vapor; but it will not prevent ignition in closed spaces.

Waste Disposal Method: Dispose of in accordance with federal, state and local regulations.

EPA Designations:

RCRA Hazardous Waste (40 CFR 261.33): Hazardous Waste No. U154
CERCLA Hazardous Substance (40 CFR 302.4): Not Listed
SARA Extremely Hazardous Substance (40 CFR 355): Not Listed
SARA Toxic Chemical (40 CFR 372.65): Not Listed

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: +22° F Windshield Washer Fluid

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Under normal use conditions (outdoor windshield cleaning), respiratory protection is not justified.

Protective Eye Wear: Splash goggles are recommended when handling the solution. Contact lens use is not recommended.

Protective Clothing: The selection of protective clothing and gloves is dependent upon anticipated exposure. As reported by the manufacturer, Best Glove style 725R (PVC) offers excellent protection for up to 240 minutes of complete immersion.

SECTION 9 - OTHER HAZARDOUS INFORMATION AND DEFINITIONS

OSHA PEL: The Occupational Safety and Health Administration's Permissible Exposure Limit, which is defined as the maximum concentration of contaminant to which a normal healthy individual may be exposed 8-hours per day, 40-hours per week, without experiencing adverse health effects over a working lifetime.

ACGIH TLV: American Conference of Governmental Industrial Hygienist's Threshold Limit Value, similar to the OSHA PEL but not considered a legal standard.

SECTION 10 – TRANSPORTATION INFORMATION

DOT HAZARD DESCRIPTION:

In Inner Packaging not over 5 l (1.3 gallons) CONSUMER COMMODITY, ORM-D
Per 49 CFR 173.150 (b) (3) & 173.150 (c)

MSDS Prepared by: Maxim Technologies, Inc.

Judgements as to the suitability herein for the user's purposes are necessarily the user's responsibility. Therefore, although reasonable care has been taken in the preparation of such information, Maxim Technologies, Inc., extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the intended purposes or for the consequences of its use.

Splash -20° F MSDS Sheets

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: -20° F Splash Windshield Washer Fluid

SECTION 1 - MANUFACTURER'S INFORMATION

Manufacturer: SuperClean Brands, Inc.
51 East Maryland Avenue
St. Paul, MN 55117-4615

Telephone: (651) 489-8211

Facsimile: (651) 489-8247

Transportation Emergency (for immediate information about a chemical or to seek assistance from a manufacturer): 1-800-535-5053

Date Updated: April 7, 2009

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Common Name: Windshield Washer Fluid

Product Use: Used for cleaning windshields

Product Identification: Windshield Washer Fluid

NFPA HAZARD RATINGS
HEALTH - 1
FLAMMABILITY - 3
REACTIVITY - 0
OTHER - NOT APPLICABLE

Hazardous Component*	Approximate Composition	OSHA Permissible Exposure Limit**	NIOSH REL	ACGIH Threshold Limit Value	IDLH (NIOSH)
Methanol (Methyl Alcohol) -CAS 67-56-1 -UN 1230 (DOT Guide 28)	31 percent by weight	200 ppm (260 mg/m ³) 8-Hour TWA (Skin)	200 ppm (260 mg/m ³) 8-Hour TWA 250 ppm (310 mg/m ³) Ceiling (Skin)	200 ppm (260 mg/m ³) 8-Hour TWA 250 ppm (310 mg/m ³) Short-term Exposure Limit (15-minute TWA) (Skin)	6,000 ppm (0.6 percent in air)

* The hazardous component listed is not a known or suspected human carcinogen as listed or determined by the National Agency for Research on Cancer, National Toxicological Program "NTP Seventh Annual Report on Carcinogens," or International Agency for Research on Cancer (IARC) monograph reviews. In addition, it is not considered a carcinogen by the Occupational Safety and Health Administration or the National Institute for Occupational Safety and Health.

** This MSDS contains the 1989 PEL's and from the June 1993 Air Contaminants Final Rule, specified in Tables Z-1, Z-2, and Z-3 [Federal Register; 58(124): 35338-35351; June 30, 1993].

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: -20° F Splash Windshield Washer Fluid

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 170°F (for product)

Flash Point: 93°F

Solubility in Water: Soluble

Vapor Pressure: 100 (mm Mercury) @ 21.2°F

Vapor Density: 1.11 (methanol)

Ionization Potential: 10.84 eV (methanol)

Freezing Point: -20°F

Appearance and Odor: The windshield washer is blue, and it has a mild characteristic pungent odor from the methanol. The odor threshold for methanol is 10 ppm.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flammable Limits: UEL - 36 percent for methanol LEL - 6 percent for methanol

Autoignition Temperature: 878°F for methanol

Extinguishing Media for Methanol

Small Fires: Dry chemical, carbon dioxide, water spray or alcohol resistant foam.

Large Fires: Water spray, fog or alcohol-resistant foam.

Special Fire Fighting Procedures: Move container away from fire area if you can do so without risk. Dike fire control water for later disposal; do not scatter the material. Apply cooling water to the sides of containers exposed to flames until well after the fire is out.

Unusual Fire and Explosion Hazards for Methanol: Flammable/combustible material; may be ignited by heat, spark or flame. Vapors may travel to a source of ignition and flash back. Container may explode in heat of fire. Vapor explosion and poison hazard indoors, outdoors, or in sewers. Runoff to sewer may create fire or explosion hazard.

SECTION 5 - REACTIVITY DATA

Stability/Polymerization: In a closed container, methyl alcohol is stable at room temperature and it is stable under routine handling and storage. Hazardous polymerization will not occur.

Incompatibility (Material to Avoid): Incompatible with beryllium dihydride; metals; oxidants; potassium tert-butoxide; carbon tetrachloride + metals; dichloromethane. Can react vigorously with oxidizing materials.

Explosive reaction with chloroform + sodium methoxide; diethyl zinc. Violent reaction with alkyl aluminum salts; acetylene bromide; chloroform + sodium hydroxide; CrO_3 ; cyanuric chloride; (I + ethanol + HgO); $\text{Pb}(\text{ClO}_4)_2$; HClO_4 ; P_2O_3 ; ($\text{KOH} + \text{CHCl}_3$); nitric acid¹

Hazardous Decomposition or By-products: When methanol is heated to decomposition, carbon dioxide and carbon monoxide may be produced, as well as formaldehyde may be produced, and it emits acrid smoke and irritating fumes.

¹Lewis, Richard J., Sr.: *Sax's Dangerous Properties of Industrial Materials, Eighth Edition*. New York, New York: Van Nostrand Reinhold, 1992.

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: -20° F Splash Windshield Washer Fluid

SECTION 6 - HEALTH HAZARD DATA

Routes of Entry (Methanol): The primary routes of entry are inhalation, ingestion, and absorption.

Health Hazards and Signs and Symptoms of Exposure (Methanol): Irritant to eyes, skin, and upper respiratory system. Headaches, drowsiness, dizziness, vertigo, light-headed, nausea, and vomiting. Visual disturbance, optic nerve damage, and blindness. Skin exposure hazard.

Target Organs: Central nervous system, digestive tract, eyes, and skin.

Acute Effects: Eye irritation. Inhalation can result nose irritation, headache, fatigue, nausea, visual impairment or complete and possible blindness, acidosis, convulsions, circulatory collapse, respiratory fatigue, and death. Ingestion can cause gastrointestinal (GI) irritation followed by the symptoms described for inhalation and possible kidney impairment. Skin contact results in a cold sensation, dryness, and cracking, possibly leading to dermatitis. Methyl alcohol may be absorbed through the skin and may cause headache, fatigue, and visual disturbances. Eye contact results in irritation with lacrimation, inflamed lids, and photophobia.

Chronic Effects: Chronic exposure may result in visual impairment or blindness.

Medical Conditions Generally Aggravated by Exposure: Ocular, respiratory, or dermal disorders may be aggravated by methanol exposure.

Emergency and First Aid Procedures:

Eyes: Rinse with water 15 to 20 minutes, seek medical assistance.
Skin: Flush with water for 15 minutes.
Inhalation: Remove from source to fresh air, provide respiratory support as needed.
Ingestion: Call Physician, hospital emergency room or Poison Control Center immediately.

GET PROMPT MEDICAL ATTENTION

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in Case Material is Released or Spilled:

- Keep unnecessary people away; isolate hazard area and deny entry.
- Stay upwind; keep out of low areas.
- Shut off ignition sources; no flares, smoking or flames in hazard area.
- Positive pressure self-contained breathing apparatus and chemical protective clothing is recommended for personnel involved in clean-up procedures with no fire.
- Do not walk through spilled material; stop leak if it can be done without risk.
- Water spray may reduce vapor; but it will not prevent ignition in closed spaces.

Waste Disposal Method: Dispose of in accordance with federal, state and local regulations.

EPA Designations:

RCRA Hazardous Waste (40 CFR 261.33): Hazardous Waste No. U154
CERCLA Hazardous Substance (40 CFR 302.4): Not Listed
SARA Extremely Hazardous Substance (40 CFR 355): Not Listed
SARA Toxic Chemical (40 CFR 372.65): Not Listed

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: -20° F Splash Windshield Washer Fluid

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Under normal use conditions (outdoor windshield cleaning), respiratory protection is not justified.

Protective Eye Wear: Splash goggles are recommended when handling the solution. Contact lens use is not recommended.

Protective Clothing: The selection of protective clothing and gloves is dependent upon anticipated exposure. As reported by the manufacturer, Best Glove style 725R (PVC) offers excellent protection for up to 240 minutes of complete immersion.

SECTION 9 - OTHER HAZARDOUS INFORMATION AND DEFINITIONS

OSHA PEL: The Occupational Safety and Health Administration's Permissible Exposure Limit, which is defined as the maximum concentration of contaminant to which a normal healthy individual may be exposed 8-hours per day, 40-hours per week, without experiencing adverse health effects over a working lifetime.

ACGIH TLV: American Conference of Governmental Industrial Hygienist's Threshold Limit Value, similar to the OSHA PEL but not considered a legal standard.

SECTION 10 – TRANSPORTATION INFORMATION

DOT HAZARD DESCRIPTION:

In inner packaging not over 5 L (1.3 gallons) Consumer commodity, ORM-D
Per 49 CFR 173.150 (b) (3) & 173.150 (c)

MSDS Prepared by: Maxim Technologies, Inc.

Judgments as to the suitability herein for the user's purposes are necessarily the user's responsibility. Therefore, although reasonable care has been taken in the preparation of such information, Maxim Technologies, Inc., extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the intended purposes or for the consequences of its use.

Splash -25° F MSDS Sheets

MATERIAL SAFETY DATA SHEET
MATERIAL IDENTITY: -25° F Splash Windshield Washer Fluid

SECTION 1 - MANUFACTURER'S INFORMATION

Manufacturer: SuperClean Brands, Inc.
51 East Maryland Avenue
St. Paul, MN 55117-4615

Telephone: (651) 489-8211

Facsimile: (651) 489-8247

Transportation Emergency (for immediate information about a chemical or to seek assistance from a manufacturer): 1-800-535-5053

Date Updated: December 12, 2007

SECTION 2 - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

Common Name: Windshield Washer Fluid

Product Use: Used for cleaning windshields

Product Identification: Windshield Washer Fluid

NFPA HAZARD RATINGS
HEALTH - 1
FLAMMABILITY - 3
REACTIVITY - 0
OTHER - NOT APPLICABLE

Hazardous Component*	Approximate Composition	OSHA Permissible Exposure Limit**	NIOSH REL	ACGIH Threshold Limit Value	IDLH (NIOSH)
Methanol (Methyl Alcohol) -CAS 67-56-1 -UN 1230 (DOT Guide 28)	34 percent (by weight)	200 ppm (260 mg/m ³) 8-Hour TWA (Skin)	200 ppm (260 mg/m ³) 8-Hour TWA 250 ppm (310 mg/m ³) Ceiling (Skin)	200 ppm (260 mg/m ³) 8-Hour TWA 250 ppm (310 mg/m ³) Short-term Exposure Limit (15-minute TWA) (Skin)	6,000 ppm (0.6 percent in air)

* The hazardous component listed is not a known or suspected human carcinogen as listed or determined by the National Agency for Research on Cancer, National Toxicological Program "NTP Seventh Annual Report on Carcinogens," or International Agency for Research on Cancer (IARC) monograph reviews. In addition, it is not considered a carcinogen by the Occupational Safety and Health Administration or the National Institute for Occupational Safety and Health.

** This MSDS contains the 1989 PEL's and from the June 1993 Air Contaminants Final Rule, specified in Tables Z-1, Z-2, and Z-3 [Federal Register; 58(124):35338-35351; June 30, 1993].

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: -25° F Splash Windshield Washer Fluid 6/1Gallon

SECTION 3 - PHYSICAL/CHEMICAL CHARACTERISTICS

Boiling Point: Approximately 170°F (for product)

Flash Point: 90°F

Solubility in Water: Soluble

Vapor Pressure: 100mm @ 21.2° (methanol)

Vapor Density: 1.11 (methanol)

Ionization Potential: 10.84 eV (methanol)

Freezing Point: -25°F

Appearance and Odor: The windshield washer is blue, and it has a mild characteristic pungent odor from the methanol. The odor threshold for methanol is 10 ppm.

SECTION 4 - FIRE AND EXPLOSION HAZARD DATA

Flammable Limits: UEL - 36 percent for methanol LEL - 6 percent for methanol

Auto ignition Temperature: 878°F for methanol

Extinguishing Media for Methanol

Small Fires: Dry chemical, carbon dioxide, water spray or alcohol resistant foam.

Large Fires: Water spray, fog or alcohol-resistant foam.

Special Fire Fighting Procedures: Move container away from fire area if you can do so without risk. Dike fire control water for later disposal; do not scatter the material. Apply cooling water to the sides of containers exposed to flames until well after the fire is out.

Unusual Fire and Explosion Hazards for Methanol: Flammable/combustible material; may be ignited by heat, spark or flame. Vapors may travel to a source of ignition and flash back. Container may explode in heat of fire. Vapor explosion and poison hazard indoors, outdoors, or in sewers. Runoff to sewer may create fire or explosion hazard.

SECTION 5 - REACTIVITY DATA

Stability/Polymerization: In a closed container, methyl alcohol is stable at room temperature and it is stable under routine handling and storage. Hazardous polymerization will not occur.

Incompatibility (Material to Avoid): Incompatible with beryllium dihydride; metals; oxidants; potassium tert-butoxide; carbon tetrachloride + metals; dichloromethane. Can react vigorously with oxidizing materials.

Explosive reaction with chloroform + sodium methoxide; diethyl zinc. Violent reaction with alkyl aluminum salts; acetylene bromide; chloroform + sodium hydroxide; CrO_3 ; cyanuric chloride; (I + ethanol + HgO); $\text{Pb}(\text{ClO}_4)_2$; HClO_4 ; P_2O_5 ; ($\text{KOH} + \text{CHCl}_3$); nitric acid¹

Hazardous Decomposition or By-products: When methanol is heated to decomposition, carbon dioxide and carbon monoxide may be produced, as well as formaldehyde may be produced, and it emits acrid smoke and irritating fumes.

¹Lewis, Richard J., Sr.: *Sax's Dangerous Properties of Industrial Materials, Eighth Edition*. New York, New York: Van Nostrand Reinhold, 1992.

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: -25° F Splash Windshield Washer Fluid 6/1 Gallon

SECTION 6 - HEALTH HAZARD DATA

Routes of Entry (Methanol): The primary routes of entry are inhalation, ingestion, and **absorption**.

Health Hazards and Signs and Symptoms of Exposure (Methanol): Irritant to eyes, skin, and upper respiratory system. Headaches, drowsiness, dizziness, vertigo, light-headed, nausea, and vomiting. Visual disturbance, optic nerve damage, and blindness. Skin exposure hazard.

Target Organs: Central nervous system, digestive tract, eyes, and skin.

Acute Effects: Eye irritation. Inhalation can result nose irritation, headache, fatigue, nausea, visual impairment or complete and possible blindness, acidosis, convulsions, circulatory collapse, respiratory fatigue, and death. Ingestion can cause gastrointestinal (GI) irritation followed by the symptoms described for inhalation and possible kidney impairment. Skin contact results in a cold sensation, dryness, and cracking, possibly leading to dermatitis. Methyl alcohol may be absorbed through the skin and may cause headache, fatigue, and visual disturbances. Eye contact results in irritation with lacrimation, inflamed lids, and photophobia.

Chronic Effects: Chronic exposure may result in visual impairment or blindness.

Medical Conditions Generally Aggravated by Exposure: Ocular, respiratory, or dermal disorders may be aggravated by methanol exposure.

Emergency and First Aid Procedures:

Eyes:	Rinse with water 15 to 20 minutes, seek medical assistance.
Skin:	Flush with water for 15 minutes.
Inhalation:	Remove from source to fresh air, provide respiratory support as needed.
Ingestion:	Call Physician, hospital emergency room or Poison Control Center immediately.

GET PROMPT MEDICAL ATTENTION

SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be Taken in Case Material is Released or Spilled:

- Keep unnecessary people away; isolate hazard area and deny entry.
- Stay upwind; keep out of low areas.
- Shut off ignition sources; no flares, smoking or flames in hazard area.
- Positive pressure self-contained breathing apparatus and chemical protective clothing is recommended for personnel involved in clean-up procedures with no fire.
- Do not walk through spilled material; stop leak if it can be done without risk.
- Water spray may reduce vapor; but it will not prevent ignition in closed spaces.

Waste Disposal Method: Dispose of in accordance with federal, state and local regulations.

EPA Designations:

RCRA Hazardous Waste (40 CFR 261.33): Hazardous Waste No. U154
CERCLA Hazardous Substance (40 CFR 302.4): Not Listed
SARA Extremely Hazardous Substance (40 CFR 355): Not Listed
SARA Toxic Chemical (40 CFR 372.65): Not Listed

MATERIAL SAFETY DATA SHEET

MATERIAL IDENTITY: -25° F Splash Windshield Washer Fluid 6/1 Gallon

SECTION 8 - SPECIAL PROTECTION INFORMATION

Respiratory Protection: Under normal use conditions (outdoor windshield cleaning), respiratory protection is not justified.

Protective Eye Wear: Splash goggles are recommended when handling the solution. Contact lens use is not recommended.

Protective Clothing: The selection of protective clothing and gloves is dependent upon anticipated exposure. As reported by the manufacturer, Best Glove style 725R (PVC) offers excellent protection for up to 240 minutes of complete immersion.

SECTION 9 - OTHER HAZARDOUS INFORMATION AND DEFINITIONS

OSHA PEL: The Occupational Safety and Health Administration's Permissible Exposure Limit, which is defined as the maximum concentration of contaminant to which a normal healthy individual may be exposed 8-hours per day, 40-hours per week, without experiencing adverse health effects over a working lifetime.

ACGIH TLV: American Conference of Governmental Industrial Hygienist's Threshold Limit Value, similar to the OSHA PEL but not considered a legal standard.

SECTION 10 – TRANSPORTATION INFORMATION

DOT HAZARD DESCRIPTION:

In inner packaging not over 5 L (1.3 gallons) Consumer commodity, ORM-D
Per 49 CFR 173.150 (b) (3) & 173.150 (c)

MSDS Prepared by: Maxim Technologies, Inc.

Judgments as to the suitability herein for the user's purposes are necessarily the user's responsibility. Therefore, although reasonable care has been taken in the preparation of such information, Maxim Technologies, Inc., extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the intended purposes or for the consequences of its use.